

JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220

Phone 800-527-8482 or 903-832-2581

Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com

Typical Specification

JCM 801 Expansion Joint

Expansion Joints shall be of the externally guided, slip joint type, permitting up to 10 inches of concentrated pipe movement. The packing gland shall have alternate rings of lubricated flax and rubber specially compounded for use with water, salt solutions, mild acids, bases, natural gas and sewage. The body of the expansion joint shall have a shop coat primer. The slip pipe shall be machined and be chrome plated. Expansion Joints shall be JCM 801 or approved equal.

JCM 800 Series Expansion Joints are ANSI/NSF Standard 61 Certified.



JCM 801 Expansion Joint

This typical specification, provided by JCM Industries, is a proposed guideline for use by specifying agencies to ensure significant design and material features of this product are included within the agencies' individual specifications.



Effective 07.14.10

JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220

Phone 800-527-8482 or 903-832-2581

Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com

Material Specification

JCM 801 Expansion Joint

Body Material: ASTM A-36 Carbon Steel

Slip Pipe: Carbon Steel - Machined and chrome plated

Gasket and Flax: 1/2" square packing Buna-N rubber, 55 - 60 durometer, compounded for use with water, salt solutions, mild acids, bases and sewage. Flax: Gurlock 1/2" waxed, braided cord (hemp).

Limit Rods: Grade B-7

Finish: Heavy coat of corrosion resistant primer.

JCM 800 Series Expansion Joints are ANSI/NSF Standard 61 and ANSI/NSF Standard 61 Annex G Certified
Information based on data available at the date printed below and subject to change without notice.



Effective 07.14.10