

## JCM Industries, Inc.

Fittings & Fabrications for Repair - Connection - Branching All Types and Sizes of Pipe

JCM Industries, Inc. P.O. Box 1220 - Nash, TX 75569-1220

Office: 903-832-2581, Fax: 903-838-6260

www.jcmindustries.com

# Email: sales@jcmindustries.com

## JCM 114 FABRICATED MECHANICAL JOINT REPAIR SLEEVE

For the repair of cast iron bells, split or leaking coupling and weld joints, flanged pipe joints or straight runs of pipe without costly shutdown or disruption to critical service.

No Shutdown or Interruption of Critical Service - by implementing a split fabricated mechanical joint design, the JCM 114 prevents costly down time and service disruption.

True Mechanical Joint Design - heavy fabricated steel body and pusher gland construction prevents the warpage and distortion experienced by repair sleeves using the split steel coupling designs.

Custom Built For Specific Application - this versatile mechanical joint fitting is built to meet the specific requirements of special applications. Eliminates lost time due to field or factory modifications.

Strong and Lightweight - the 114 sleeves are ideal for installations where strength, weight and continued service are critical. The reduced weight of high strength steel aids in installation and handling as well as minimizing weight load on the pipe.



Call Toll Free: 800-527-8482

Fax Toll Free: 800-874-9524

Available in Three Styles - the 114 MJ Split Repair Sleeve for use on straight runs of pipe and the 114 MJ Bell Repair Sleeve which is fabricated to accommodate the specific dimensions of the bell, collar or coupling to be repaired. The JCM 114 MJ Repair Sleeve can also be fabricated to accommodate two different O.D.'s of pipe.

Optional Materials - the 114 is available in carbon steel with special coatings and fasteners, or is available fabricated of 304 stainless steel or 316 stainless steel.

Sizes & Configurations - the 114 is available for pipe sizes 4" and larger. Custom design and product submittal for unique or problematic applications provided by JCM Engineering Group.







### **JCM 114 Fabricated Mechanical Joint Repair Sleeve**

Body: ASTM A36, ASTM A516 Grade 70 or equal. Optional 304 or 316 Stainless Steel

Glands: ASTM A36 Steel. Optional 304 or 316 Stainless Steel

Bolts: Corrosion resistant, high strength low alloy ASTM A242, A193 B5, B7

Optional A193 B8 304 stainless steel or 316 stainless steel

**Gasket:** Nitrile - Compounded for use with water, salt solutions, mild acids and bases.

**Finish:** Heavy coat of corrosion resistant shop coat primer.

Optional Fusion Epoxy Coating available per ANSI/AWWA C213


#### **HOW TO SPECIFY:**

For specific product submittal, the following information must be furnished:

#### JCM 114 Mechanical Joint Split Repair Sleeve


The following information must be furnished.

Type of Pipe
Pipe Outside Diameter
Length Requirements
Line Content and Temperature
Line Pressure
Finish or Coating Requirements



#### JCM 114 Mechanical Joint Bell Repair Sleeve The following information must be furnished.

Type of Pipe
Spigot or Pipe Outside Diameter
Largest Bell, Coupling, Flange Dimension
Length Requirements
Line Content and Temperature
Line Pressure
Finish or Coating Requirements









Available in 304 or 316 stainless steel

Typical Application: Repair Temporary/Permanent Repair Pipe In Service

Cracked/Broken Pipe Joints Splits Holes Failed MJ Joints, Fittings or Couplings

For application parameters, contact JCM Engineered and Technical Sales 800-527-8482 or 903-832-2581

