

JCM 131 All Stainless Steel Universal Clamp Couplings

JCM 131 All Stainless Steel Clamp Coupling with larger bolts and heavier lug - especially for piping systems that are exposed to hot soils or corrosive environments. JCM All Stainless Clamps provide the corrosion resistance of stainless to this means of repairing and connecting pipe.



Image reflects 6" width

Nom. Pipe Size	Clamp O.D. Range	131 Stainless Steel Universal Clamp Coupling Clamp Number	Clamp Width - Approximate Weight						
			6"	7"	12"	15"	18"	24"	30"
			Lbs.#	Lbs.#	Lbs.#	Lbs.#	Lbs.#	Lbs.#	Lbs.#
1-1/2	1.88 - 2.15	0190	\$158.70	-	250.30	-	-	-	-
			5#		10#				
2 2-1/2	2.35 - 2.63 2.70 - 3.13	0238 0275	158.70	168.60	257.60	310.00	-	-	-
			5#	6#	10#	12#			
3	3.46 - 3.70 3.73 - 4.13	0350 0400	183.70	205.70	312.00	369.00	-	-	-
			6#	7#	11#	13#			
4	4.45 - 4.75 4.74 - 5.14 4.95 - 5.35 5.22 - 5.62	0450 0480 0500 0525	215.30	226.60	369.50	405.30	561.20	711.90	964.50
			6#	7#	12#	14#	18#	24#	28#
6	5.95 - 6.35 6.56 - 6.96 6.85 - 7.25 7.05 - 7.45 7.45 - 7.85	0600 0663 0690 0710 0745	253.00	263.20	434.40	480.00	665.90	837.10	1,079.70
			7#	8#	13#	16#	21#	26#	31#
8	7.95 - 8.35 8.54 - 8.94 8.99 - 9.39 9.27 - 9.67 9.90 - 10.30	0800 0863 0905 0940 1000	290.70	302.60	493.30	571.40	748.80	931.90	1,191.80
			8#	9#	15#	19#	24#	30#	38#
8 - 10	10.60 - 11.00 11.04 - 11.44 11.34 - 11.74 11.75 - 12.15 12.00 - 12.40	1075 1110 1140 1175 1200	-	393.20	686.30	706.90	1,023.50	1,301.50	1,541.70
				15#	26#	31#	39#	42#	60#
12	12.60 - 13.02 13.10 - 13.50 13.40 - 13.80 13.70 - 14.10 14.00 - 14.40	1275 1320 1340 1370 1400	-	441.60	763.30	811.90	1,115.30	1,462.30	1,766.90
				17#	28#	34#	42#	56#	68#
Number of Bolts			2	2	4	4	6	8	10

HOW TO ORDER

1. Determine O.D. of pipe.
2. Select proper clamp O.D. range and band width.
3. Determine Model Number.
4. Specify clamp number. Example: To fit Cast Iron pipe, 6.90 O.D. with 6" width, order: 131-0690-6

Clamps do not prevent lateral movement of pipe. Applications in which the pipe may move out of the clamp, proper anchorage of the pipe must be provided.

Clamps widths 7" and 15" use 5/8" bolts

Available Options Upon Request Models 131-132

- Pipe sizes and ranges not listed
- Conductive Buttons
- Specialty Gaskets
- Tapped clamps, see page 14

