

JCM 202 Long Steel Couplings for Steel Pipe Sizes

Nom Pipe Size (IN)	Pipe OD Range (IN)	Sleeve Length X Thickness	No. of Bolts	Catalog Number	List Price Each	Appr Wt Each Lbs
2	2.38	.157 X 12	3	202-023811	\$ 188.40	15
2-1/2	2.88	.197 X 12	3	202-028811	198.80	20
3	3.50	.157 X 12	4	202-035011	253.30	16
4	4.50	.157 X 12	4	202-045011	317.60	22
6	6.63	1/4 X 16	6	202-066311	638.50	45
8	8.63	1/4 X 16	6	202-086311	849.70	54
10	10.75	1/4 X 16	8	202-107511	1,049.80	81
12	12.75	1/4 X 16	8	202-127511	1,224.70	119

Smaller and Larger Sizes available upon request

Note: Applications in which pipe may move out of the coupling, correct anchorage of the pipe must be provided



Material Specifications

Middle Rings: 2" - 12" Steel per ASTM A36

14" and larger Steel per ASTM A36

Followers: 2" - 12" Ductile Iron ASTM A536

14" and larger Steel per ASTM A36

Bolts: Nominal sizes 2" and larger: minimum 5/8" bolts ASTM A242/ANSI/AWWA C111/A21.11 corrosion resistant, high strength low alloy; heavy hex nuts A563 per ANSI/AWWA C219. Available Options: Electro-coated Powercron 590-534; Stainless Steel 18-8 Type 304

Gaskets: Nitrile Butadiene Rubber (NBR, Buna-N) per ASTM D2000. Molded virgin rubber. Gasket temperature range -40°F to 212°F (-40°C - 100°C) Recommended for water, salt solutions, mild acids, bases, sewage and natural gas. Available Options: EPDM

Finish: Heavy coat of corrosion resistant shop coat primer. Optional fusion applied epoxy per ANSI/AWWA C213.

Pressure: Rated for 250 PSI working pressure when installed per manufacturer's instructions. Please contact JCM concerning pressure rating on specific sizes.