

JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220
Phone 800-527-8482 or 903-832-2581
Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com

Typical Specification

JCM 412 Fabricated Tapping Sleeve

Tapping Sleeves shall be high strength with body fabricated of ASTM A36, A516 GR 70 or equal, which conforms to and reinforces the pipe. The sleeve shall have as a minimum 7/8" wide gasket of Nitrile Butadiene Rubber (NBR, Buna-N) per ASTM D2000 with hydromechanical activated lip, captured in a groove around the outlet; a 3/4" test outlet and oval neck track head bolts and nuts.

Flanged outlet shall be per ANSI/AWWA C207 Class D, ANSI 150 lb. Drilling, recessed for tapping valve per MSS-SP60.

For outlet sizes 14" and larger, the gasket groove must be consistently positioned about throat of tapping waterway. Inside diameter of the gasket groove must be set back a minimum of 1" from the waterway to allow dispersal of forces generated by gasket compression. Gasket grooves machined in a circle and formed to an elliptical shape will not be an accepted equal.

Tapping Sleeves shall be JCM 412 or approved equal.

JCM 400 Series Tapping Sleeves are ANSI/NSF Standard 61, Annex G and ANSI/NSF 372 Certified. JCM 400 Series Tapping Sleeves meet MSS-SP124 and ANSI/AWWA Standard C223 Fabricated Steel and Stainless Steel Tapping Sleeves as applicable.



JCM 412 Tapping Sleeve
Image reflects 6" x 4"

This typical specification, provided by JCM Industries, is a proposed guideline for use by specifying agencies to ensure significant design and material features of this product are included within the agencies' individual specifications.



JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220

Phone 800-527-8482 or 903-832-2581

Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com

Material Specification

JCM 412 Fabricated Tapping Sleeve

Body: Carbon Steel per ASTM A36, A516 GR 70 or equal.

Flange: Per ANSI/AWWA Standard C207 Class D, ANSI 150 lb. Drilling, recessed for tapping valve per MSS-SP60. Optional flanges available upon request.

Bolts: Sleeve sizes 7.45 and smaller = 5/8", sleeve sizes 9.05 and larger = 3/4"

Gasket: Nitrile Butadiene Rubber (NBR, Buna-N) per ASTM D2000. Molded virgin rubber with a pressure activated hydromechanical design. Gasket is bonded into a cavity for internal and external retention. Gasket temperature range -40°F to 212°F (-40°C - 100°C) Gasket suitable for water, salt solutions, mild acids, bases, and sewage. Optional gasket materials available. Contact JCM Industries, Inc.

Service

Rating: 2" to 12" Outlets: 175 PSI. Higher service rating available for specific applications and sizes. Higher test and working pressure ratings available upon request, contact JCM Industries.

Select Finish and Hardware Options:

Finishes

- Heavy coat of corrosion resistant shop coat primer.
- Fusion applied epoxy coating, minimum 12 mils thickness per ANSI/AWWA Standard C213 Fusion Bonded Epoxy Coatings and Linings for Steel Water Pipe and Fittings.

Bolts

- Electro Coated Powercron 590-534, high strength low alloy oval neck track head bolt per ASTM A242 and nuts (per ASTM A563) or equal.
- Stainless Steel Type 304
- Stainless Steel Type 316

JCM 400 Series Tapping Sleeves meet MSS-SP124 and ANSI/AWWA Standard C223 Fabricated Steel and Stainless Steel Tapping Sleeves as applicable.

